

A UNIQUE LOW-GLOSS TEXTURED COATING

Beckry®Tex



Beckry®Tex textured/wrinkle coatings are the culmination of 30+ years of research and development by the Beckers Group. Beckry®Tex is a warranted, highly durable, high performance exterior polyester architectural coating system that is field proven with a unique, unmatched appearance. Beckry®Tex is formulated with inorganic pigments and used with a corrosion resistant primer, resulting in a higher level of UV resistance which creates a superior level of color and gloss stability. It is easy to form while still maintaining a structure that is resistant to cracking and dirt pickup. Beckry®Tex provides superior weatherability and makes an ideal finish for any commercial, residential or industrial metal architectural project.



www.beckers-group.com

2526 Delta Lane, Elk Grove, IL 60007 | P: 847-766-3555 | F: 847-766-3595 | info-beckersspecialty@beckers-group.com

Beckry®Tex

Stock Colors



Note: The colors on this card are produced as closely as possible to the Beckry®Tex paint colors and are for guidance only. Actual color panels are available upon request. For more information on additional colors or custom colors, please contact Customer Service.

Product Specifications

- Pencil Hardness (ASTM D 3363¹): F-2H, Eagle Turquoise
- Gloss @ 60° (ASTM D 523): 2 to 6
- Solvent Resistance (ASTM D 5402): 100+ MEK double rubs
- Reverse Impact Resistance (ASTM D 2794²): 1.5 x metal thickness/no pick-off or cracking
- Flexibility/T-Bend (ASTM D 4145²): 2T no pick-off
- Metal Marking Resistance: Excellent
- Humidity Resistance (ASTM D 2247, ASTM D714): No blistering, loss of adhesion, or discoloration after 1500 hours exposure to 100% relative humidity
- Salt Spray Resistance (ASTM B 117, ASTM D714): None or few #8 blisters and no more than 1/16" creepage from a score line using 5% salt solution for 1500 hours
- South Florida Exposure: 2 years @ 45°/no blistering, cracking, peeling or splitting. Less than 2.0 ΔE, 60% gloss retention
- QUV-A Accelerated Weathering (ASTM G154, ASTM D2244): Less than 2.0 ΔE, 60% gloss retention for 2000 hours

All product specifications are based on a flat panel with proper pretreatment. testing has been conducted on two coat HDG Steel/ Galvalume®/Aluminum. 1-American Society for Testing and Materials. 2-Beckry®Tex was not designed to bridge breaks in the substrate. Beckers group disclaims all implied warranties. Beckers Group will not be liable for any special, incidental or consequential damages. Beckry®Tex MSDS and PDS are available upon request. Beckry®Tex is a registered trademark of AB Wilh. Becker Galvalume® is a registered trademark of BEIC International, Inc. Beckers rainbow logotype, and Beckry are trademarks owned by AB Wilh.

Substrates

- Galvalume®
- Galvanized Steel
- Aluminum

Benefits

- Unique Appearance
- High Weatherability
- Color Consistency
- Durability

Suggested Applications

- Standing Seam Roofs
- Metal Tile Roofs
- Residential, Commercial and Industrial Roofs



www.beckers-group.com

2526 Delta Lane, Elk Grove, IL 60007 | P: 847-766-3555 | F: 847-766-3595 | info-beckerspecialty@beckers-group.com